

Qty. Description

1 UPS 32-80 180



Note! Product picture may differ from actual product

Product No.: [95906444](#)

The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing.

The bearings are lubricated by the pumped liquid.

The pump has 3-step speed selector.

The pump is characterized by:

- * Ceramic shaft and radial bearings.
- * Carbon axial bearing.
- * Stainless steel rotor can and bearing plate.
- * Corrosion-resistant impeller, Composite.
- * Cast iron pump housing.

The motor is a 1-phase motor.

No additional motor protection is required.

Liquid:

Pumped liquid: Water
Liquid temperature range: -25 .. 110 °C
Selected liquid temperature: 60 °C
Density: 983.2 kg/m³

Technical:

Rated flow: 5.14 m³/h
Rated head: 5.19 m
TF class: 110

Materials:

Pump housing: Cast iron
EN 1561 EN-GJL-200
ASTM 30 B
Impeller: Composite
PES+30% GF

Installation:

Range of ambient temperature: 0 .. 40 °C
Maximum operating pressure: 10 bar
Type of connection: G
Size of connection: 2 inch
Pressure rating for connection: PN 10
Port-to-port length: 180 mm

Electrical data:

Power input in speed 1: 135 W
Power input in speed 2: 200 W
Max. power input: 220 W



Company name:

Created by:

Phone:


Date:

13/07/2024


Qty.	Description
------	-------------

1	Mains frequency: 50 Hz
	Rated voltage: 1 x 230 V
	Current in speed 1: 0.6 A
	Current in speed 2: 0.9 A
	Current in speed 3: 0.98 A
	Capacitor size - run: 4 µF
	Enclosure class (IEC 34-5): X2D
	Insulation class (IEC 85): F
	Built-in motor protection: CONTACT
	Others:
	Terminal box position: 9H
	Net weight: 4.57 kg
	Gross weight: 4.85 kg
	Shipping volume: 0.009 m³


95906444 UPS 32-80 180 50 Hz






Pumped liquid = Water
 Liquid temperature during operation = 60 °C
 Density = 983.2 kg/m³





Description	Value
General information:	
Product name:	UPS 32-80 180
Product No:	95906444
EAN number:	5700310346649
Technical:	
Speed no:	3
Rated flow:	5.14 m³/h
Rated head:	5.19 m
Maximum head:	80 dm
TF class:	110
Materials:	
Pump housing:	Cast iron
Pump housing:	EN 1561 EN-GJL-200
Pump housing:	ASTM 30 B
Impeller:	Composite
Impeller:	PES+30% GF
Installation:	
Range of ambient temperature:	0 .. 40 °C
Maximum operating pressure:	10 bar
Type of connection:	G
Size of connection:	2 inch
Pressure rating for connection:	PN 10
Port-to-port length:	180 mm
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 110 °C
Selected liquid temperature:	60 °C
Density:	983.2 kg/m³
Electrical data:	
Power input in speed 1:	135 W
Power input in speed 2:	200 W
Max. power input:	220 W
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Current in speed 1:	0.6 A
Current in speed 2:	0.9 A
Current in speed 3:	0.98 A
Capacitor size - run:	4 µF
Enclosure class (IEC 34-5):	X2D
Insulation class (IEC 85):	F
Built-in motor protection:	CONTACT
Thermal protec:	INT.
Others:	
Terminal box position:	9H
Net weight:	4.57 kg
Gross weight:	4.85 kg
Shipping volume:	0.009 m³



Pumped liquid = Water
Liquid temperature during operation = 60 °C
Density = 983.2 kg/m³



95906444 UPS 32-80 180 50 Hz



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.