




99159862 HYDRO MULTI-S 2 CM15-3 50 Hz





Losses in fittings and valves not included
 Pumped liquid = Water
 Liquid temperature during operation = 20 °C
 Density = 998.2 kg/m³



Description	Value
General information:	
Product name:	HYDRO MULTI-S 2 CM15-3
Product No:	99159862
EAN number:	5712607849658
Technical:	
Min flow system:	3 m³/h
Max flow system:	30 m³/h
Maximum head:	33 m
Approvals:	CE
Pump name:	CM15-3
Non-ret. valve:	NO
Number of pumps:	2
Materials:	
Manifold:	Galvanised steel
Installation:	
Maximum operating pressure:	10 bar
Pipe connection:	2.5
Earth connection:	PE
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	5 .. 70 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Mains frequency:	50 Hz
Rated voltage:	3 x 380-415 V
Method of start:	DOL
Enclosure class (IEC 34-5):	IP54
Others:	
Net weight:	109 kg
Gross weight:	156 kg
Sales region:	Thailand



Losses in fittings and valves not included
Pumped liquid = Water
Liquid temperature during operation = 20 °C
Density = 998.2 kg/m³



99159862 HYDRO MULTI-S 2 CM15-3 50 Hz

