

Description	Value
General information:	
Product name:	UP 20-15 N 150
Product No:	59641500
EAN number:	5708601058738
Technical:	
Speed no:	1
Rated flow:	1.13 m³/h
Rated head:	0.63 m
Maximum head:	15 dm
TF class:	95
Approvals:	CE,VDE,EAC,WEEE
Materials:	
Pump housing:	Stainless steel
Pump housing:	EN 1.4301
Pump housing:	AISI 304
Impeller:	Composite
Impeller:	PES+30% GF
Installation:	
Range of ambient temperature:	0 .. 40 °C
Amb. max at 80 dgr C liquid:	40 °C
Maximum operating pressure:	10 bar
Type of connection:	G
Size of connection:	1 1/4 inch
Pressure rating for connection:	PN 10
Port-to-port length:	150 mm
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	2 .. 110 °C
Selected liquid temperature:	60 °C
Density:	983.2 kg/m³
Electrical data:	
Max. power input:	65 W
Mains frequency:	50 Hz
Rated voltage:	1 x 230 V
Current in speed 3:	0.28 A
Capacitor size - run:	2 µF
Enclosure class (IEC 34-5):	IP44
Insulation class (IEC 85):	F
Built-in motor protection:	NONE
Thermal protec:	IMP.
Others:	
Terminal box position:	9H
Net weight:	2.05 kg
Gross weight:	2.16 kg
Shipping volume:	0.004 m³
Danish VVS No.:	380615100
Swedish RSK No.:	5803011
Finnish LVI No.:	4615604
Norwegian NRF no.:	9042209

