







96503191 CR 10-8 A-A-A-E-HQQE 60 Hz



Pumped liquid = Water
 Liquid temperature during operation = 20 °C
 Density = 998.2 kg/m³



Description	Value
General information:	
Product name:	CR 10-8 A-A-A-E-HQQE
Product No:	96503191
EAN number:	5700396265537
Technical:	
Pump speed on which pump data are based:	3526 rpm
Rated flow:	12.1 m³/h
Rated head:	95.7 m
Maximum head:	119 m
Stages:	8
Impellers:	8
Number of reduced-diameter impellers:	0
Low NPSH:	N
Pump orientation:	Vertical
Shaft seal arrangement:	Single
Code for shaft seal:	HQQE
Approvals:	CE,EAC,UKCA,SEPRO
Approvals for drinking water:	WRAS,ACS
Curve tolerance:	ISO9906:2012 3B
Pump version:	A
Model:	A
Materials:	
Base:	Cast iron
Base:	EN 1561 EN-GJL-200
Base:	ASTM A48-25B
Impeller:	Stainless steel
Impeller:	EN 1.4301
Impeller:	AISI 304
Material code:	A
Code for rubber:	E
Bearing:	SIC
Installation:	
Maximum ambient temperature:	60 °C
Maximum operating pressure:	16 bar
Max pressure at stated temp:	16 bar / 120 °C
Max pressure at stated temp:	16 bar / -20 °C
Type of connection:	Oval / Rp
Size of inlet connection:	1 1/2 inch
Size of outlet connection:	1 1/2 inch
Pressure rating for connection:	PN 16
Flange size for motor:	FF265
Connect code:	A
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-20 .. 120 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor standard:	IEC
Motor type:	132SC
Rated power - P2:	5.5 kW
Power (P2) required by pump:	5.5 kW
Mains frequency:	60 Hz
Rated voltage:	3 x 220-277D/380-480Y V
Rated current:	18,4-16,2/10,6-9,30 A
Starting current:	1020-1480 %





Company name:

Created by:

Phone:

Date:

19/07/2024

Description	Value
Cos phi - power factor:	0.90-0.80
Rated speed:	3510-3550 rpm
IE Efficiency class:	NEMA Premium / IE3 60Hz
Motor efficiency at full load:	89.5 %
Motor efficiency at 3/4 load:	90.3-89.9 %
Motor efficiency at 1/2 load:	89.9-87.9 %
Number of poles:	2
Enclosure class (IEC 34-5):	55 Dust/Jetting
Insulation class (IEC 85):	F
Built-in motor protection:	PTC
Motor No:	85U07417
Controls:	
Frequency converter:	None
Others:	
Terminal box position:	6
Minimum efficiency index, MEI ≥:	0.70
Net weight:	86 kg
Gross weight:	108 kg
Shipping volume:	0.285 m ³